

Prüfbericht 366-0345-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 001046

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16605130-78

Stand: 02.02.2017



Seite: 1 von 2

Manufacturer : CITROEN, FIAT, PEUGEOT**Wheel dates:**

Wheel size according to standard : 6 J X 16 H2 Off set(mm) : 68

Hole circle (mm)/number of holes : 130/5 centering type : centering fixed

Technical dates, short form

| version | Version name | | Centering hole (mm) | Centering material | Permissible wheel Load (kg) | Permissible rolling Circumference (mm) | Valid from Production date |
|--------------|----------------------|--------------------------|---------------------|--------------------|-----------------------------|--|----------------------------|
| | Wheel identification | Centering identification | | | | | |
| R1-1910 | R1-1910 | Without | 78 | | 1280 | 2269 | 47/14 |
| R1-1910.MWRO | R1-1910 | Without | 78 | | 1280 | 2269 | 37/16 |

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : CITROEN

Mounting parts : conical collar bolt M16x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 180 Nm

commercial type: **CITROEN JUMPER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|----------|--------------------------|-----------------------|---|
| Y | e3*2001/116*0234*.. | 96 - 130 | 215/75R16C 225/75R16C | | *) ; from e3*2001/116*0234*12; long wheel base; 1); 2); 33) |

commercial type: **JUMPER Cabine Approfondie**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|--------------------|----------|---|-----------------------|---|
| YD | e2*2007/46*0256*.. | 96 - 110 | 215/75R16C 225/75R16C 225/75R16C M+S | | *) ; from e2*2007/46*0256*04; 1); 2); 33) |

commercial type: **JUMPER, RELAY**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|--------------------|----------|---|-----------------------|---|
| Y | e3*2007/46*0046*.. | 96 - 130 | 215/75R16 225/75R16 | | *) ; from e3*2007/46*0046*10; 1); 2); 33) |
| Y | e3*2007/46*0051*.. | 96 - 130 | 215/75R16C 225/75R16C 225/75R16C M+S | | *) ; from e3*2007/46*0051*08; 1); 2); 33) |

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : FIAT

Mounting parts : conical collar bolt M16x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 180 Nm

Prüfbericht 366-0345-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 001046

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16605130-78

Stand: 02.02.2017



Seite: 2 von 2

commercial type: **FIAT DUCATO**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|----------|--------------------------|-----------------------|---|
| 250 | e3*2001/116*0232*.. | 88 - 130 | 215/75R16C 225/75R16C | | *) ; from e3*2001/116*0232*16; 1); 2); 33) |
| 250 | e3*2007/46*0044*.. | 96 - 130 | 215/75R16C 225/75R16C | | *) ; from e3*2007/46*0044*13; long wheel base; 1); 2); 33) |
| 250 | e3*2007/46*0049*.. | 96 - 130 | 215/75R16C 225/75R16C | | *) ; from e3*2007/46*0049*10; long wheel base; 1); 2); 33) |

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : PEUGEOT

Mounting parts : conical collar bolt M16x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 180 Nm

commercial type: **BOXER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|--------------------|----------|--------------------------|-----------------------|---|
| Y | e3*2007/46*0045*.. | 96 - 130 | 215/75R16C 225/75R16C | | *) ; from e3*2007/46*0045*10; long wheel base; 1); 2); 33) |
| Y | e3*2007/46*0050*.. | 96 - 130 | 215/75R16C 225/75R16C | | *) ; from e3*2007/46*0050*08; long wheel base; 1); 2); 33) |

commercial type: **PEUGEOT BOXER**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|----------|--------------------------|-----------------------|--|
| Y | e3*2001/116*0233*.. | 96 - 130 | 215/75R16C 225/75R16C | | *) ; from e3*2001/116*0233*12; not short wheel base; 1); 2); 33) |

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.