

Prüfbericht 366-0563-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000842

ANLAGE: 9.4
 Hersteller: MW Aftermarket Srl

Radtyp: 16655112-55
 Stand: 18.06.2015



Seite: 1 von 2

Manufacturer : DAIMLER (D)

Wheel dates:

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 52
 Hole circle (mm)/number of holes : 112/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1911	R1-1911	Without	66,5		850	2062	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : DAIMLER (D)

Mounting parts : spherical collar bolt M14x1,5, diameter 28,2 mm

Tightening torque for fixing parts : 180 Nm

commercial type: **Marco Polo, V-Klasse, Vito, Vito Tourer**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
639/2	e1*2007/46*0457*..	100	195/65R16C		*); V-Klasse; from e1*2007/46*0457*09; Rear-wheel drive; 1); 2); 33)
		100 - 120	205/65R16C		
		100 - 140	225/60R16C		
639/2	e1*2007/46*0457*..	65 - 100	195/65R16C		*); Vito; 1); 2); 33)
		65 - 120	205/65R16C		
		65 - 140	225/60R16C		

commercial type: **V-Klasse, Vito, Vito Tourer**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
639/4	e1*2007/46*0458*..	65 - 100	195/65R16C		*); V-Klasse; Vito; Vito Tourer; Vito Mixto; from e1*2007/46*0458*08; Front wheel drive; Rear-wheel drive; 1); 2); 33)
		65 - 120	205/65R16C		
		65 - 140	225/60R16C		

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.

**Prüfbericht 366-0563-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000842**

ANLAGE: 9.4
Hersteller: MW Aftermarket Srl

Radtyp: 16655112-55
Stand: 18.06.2015



Seite: 2 von 2

- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.