

**Prüfbericht 366-0224-16-WIRD
zur Erteilung der ECE (E1) 124R- 001071**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 16656125-77

Stand: 25.05.2016



Seite: 1 von 1

Manufacturer : IVECO**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 68

Hole circle (mm)/number of holes : 125/6 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1913	R1-1913	Without	74		1215	2171	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : IVECO

Mounting parts : conical collar nut M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 170 Nm

commercial type: **DAILY CAB 29L11..35S11..21**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
IS35SI2AA	e3*2007/46*0118*..	78-205	205/65R16C 107		1); 2); 33)
IS35SI2BA	e3*2007/46*0118*..		215/65R16 109		
			225/65R16C 112		
			235/65R16C		

commercial type: **DAILY VAN 29L11..35S11..21**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
IS35SC2AA	e3*2007/46*0120*..	78-150	205/65R16C 107		1); 2); 33)
			215/65R16 109		
			225/65R16C 112		
			235/65R16C		

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.