

**Prüfbericht 22-00175-CX-GBM-04**  
**zur Erteilung der ECE (E1) 124R- 000831**

**ANLAGE: 9.8**  
 Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29  
 Stand: 17.05.2022



Auto Service

Seite: 1 von 1

**Manufacturer : FORD**

**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2      Off set(mm) : 37,5  
 Hole circle (mm)/number of holes : 108/4      centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1923	R1-1923	Without	63,35		495	1937	47/15

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : FORD**

Mounting parts : conical collar nut M12x1,5

Tightening torque for fixing parts : 135 Nm

commercial type: **B-MAX**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JK8-LPG	e13*2007/46*1380*..	66	185/60R15		1); 2); 33)
			185/60R15 M+S		
			195/60R15		

commercial type: **B-MAX / EcoSport**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JK8	e9*2007/46*0092*..	55 - 103	185/60R15		*); Only B-Max; 1); 2); 33)
			195/60R15		
JK8	e9*2007/46*0092*..	66 - 103	195/65R15		*); Only ECOSPORT; Hatchback; Front wheel drive; 1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.