

Prüfbericht 21-00319-CX-GBM-07
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000847

ANLAGE: 9.10
 Hersteller: MW Aftermarket Srl

Radtyp: 16655114-62
 Stand: 21.04.2022



Auto Service

Seite: 1 von 1

Manufacturer : SUZUKI

Wheel dates:

Wheel size according to standard : 6 1/2 J X 16 CH Off set(mm) : 50
 Hole circle (mm)/number of holes : 114,3/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1947	R1-1947	Without	60		535	2025	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : SUZUKI

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

commercial type: **VITARA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
LY	e4*2007/46*0928*..	88	215/60R16 95		744; 1); 2); 33)

Restrictions

- 744) The tightening torque of the custom wheels' fastening elements is specified in the vehicle's operating manual. Should no tightening torque be specified there, the tightening torque quoted in the expert report shall apply.
- 1) To be kept:
- the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.