

**Prüfbericht 366-0094-16-WIRD
zur Erteilung der ECE (E1) 124R- 001136**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15605105-42

Stand: 09.03.2016



Seite: 1 von 1

Manufacturer : OPEL / VAUXHALL**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 37

Hole circle (mm)/number of holes : 105/5 centering type : centering fixed

Technical dates, short form

| version | Version name | | Centering hole (mm) | Centering material | Permissible wheel Load (kg) | Permissible rolling Circumference (mm) | Valid from Production date |
|---------|----------------------|--------------------------|---------------------|--------------------|-----------------------------|--|----------------------------|
| | Wheel identification | Centering identification | | | | | |
| R1-1952 | R1-1952 | Without | 56,5 | | 485 | 1937 | 47/14 |

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : OPEL / VAUXHALL

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 120 Nm

commercial type: **ASTRA, ASTRA+**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|--------------------|--------|-----------|-----------------------|-------------------------------------|
| B-K | e4*2007/46*0996*.. | 70-110 | 195/65R15 | | *) ; Front wheel drive; 1); 2); 33) |

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.