

**Prüfbericht 366-0099-16-WIRD**  
**zur Erteilung der ECE (E1) 124R- 001145**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16706114-88

Stand: 16.03.2016



Seite: 1 von 1

**Manufacturer** : **Nissan International S. A.**

**Wheel dates:**

Wheel size according to standard : 7 J X 16 CH Off set(mm) : 45

Hole circle (mm)/number of holes : 114,3/6 centering type : centering fixed

**Technical dates, short form**

| version | Version name         |                          | Centering hole (mm) | Centering material | Permissible wheel Load (kg) | Permissible rolling Circumference (mm) | Valid from Production date |
|---------|----------------------|--------------------------|---------------------|--------------------|-----------------------------|--|----------------------------|
|         | Wheel identification | Centering identification |                     |                    |                             |  |                            |
| R1-1966 | R1-1966              | Without                  | 66                  |                    | 926                         | 2330                                   | 47/14                      |

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : **Nissan International S. A.**

Mounting parts : conical collar nut M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 133 Nm

commercial type: **NISSAN NP300 NAVARA**

| Vehicle type | Approval           | kW       | Tires     | Restrictions of tires | Restrictions                                    |
|--------------|--------------------|----------|-----------|-----------------------|---|
| D231         | e9*2007/46*6364*.. | 120 -140 | 255/70R16 |                       | *) ; all-wheel drive; Rear-wheel drive; 1); 33) |

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.