

**Prüfbericht 366-0379-16-WIRD
zur Erteilung der ECE (E1) 124R- 001209**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15506170-92

Stand: 28.09.2016



Seite: 1 von 1

Manufacturer : Nissan International S. A., RENAULT

Wheel dates:

Wheel size according to standard : 5 J X 15 H2 Off set(mm) : 106,5

Hole circle (mm)/number of holes : 170/6 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1972	R1-1972	Without	130		900	1985	06/16

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : Nissan International S. A.

Mounting parts : Flachbundmuttern 016x1,5

Tightening torque for fixing parts : 155 Nm

commercial type: **NISSAN CABSTAR**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
F241	e9*2007/46*0030*..	90-110	195/70R15C		*) Zwillingsbereifung; 1); 2); 33)

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : RENAULT

Mounting parts : Flachbundmuttern 016x1,5

Tightening torque for fixing parts : 155 Nm

commercial type: **RENAULT MAXITY**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
F241	e9*2007/46*0035*..	81	195/70R15C		*) Zwillingsbereifung; 1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.