

Prüfbericht 366-0448-16-WIRD/N1
zur Erteilung der ECE (E1) 124R- 001227

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16705108-93

Stand: 17.05.2017



Seite: 1 von 2

Manufacturer : **CITROEN, PEUGEOT, Toyota Motor Europe NV/SA**

Wheel dates:

Wheel size according to standard : 7 J X 16 H2

Off set(mm) : 46

Hole circle (mm)/number of holes : 108/5

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1980.MWFR	R1-1980	Without	65		950	2092	29/16
R1-1980.MWRO	R1-1980	Without	65		950	2092	29/16

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : **CITROEN**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **Jumpy, Dispatch**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
V	e2*2007/46*0531*..	70 -130	215/65R16		1); 2); 33)

commercial type: **Jumpy SpaceTourer**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
V	e2*2007/46*0530*..	70 -130	215/65R16		1); 2); 33)

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : **PEUGEOT**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **Expert, Expert Traveller**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
V	e2*2007/46*0533*..	70 -130	215/65R16		1); 2); 33)

commercial type: **Expert Traveller**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
V	e2*2007/46*0532*..	70	215/65R16C		1); 2); 33)
			215/65R16C		
		70 -110	215/65R16		
			85		
		110	215/65R16C		
			215/65R16C		
		130	215/65R16C		
			215/65R16C		

Prüfbericht 366-0448-16-WIRD/N1
zur Erteilung der ECE (E1) 124R- 001227

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16705108-93

Stand: 17.05.2017



Seite: 2 von 2

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : Toyota Motor Europe NV/SA

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **PROACE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
V	e2*2007/46*0537*..	70 - 110	215/65R16		1); 2); 33)
		70 - 130	215/65R16C		
V	e2*2007/46*0538*..	70 - 110	215/65R16		1); 2); 33)
		70 - 130	215/65R16C		

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.