

**Prüfbericht 22-00175-CX-GBM-04**  
**zur Erteilung der ECE (E1) 124R- 000831**

ANLAGE: 9.10

Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29

Stand: 17.05.2022



Auto Service

Seite: 1 von 1

**Manufacturer** : **FORD****Wheel dates:**

Wheel size according to standard : 6 J X 15 CH Off set(mm) : 47,5

Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1989	R1-1989	Without	63,35		388	1815	26/17

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer** : **FORD**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 133 Nm

commercial type: **FORD KA, FORD KA+**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
KAF	e13*2007/46*1637*..	52 - 70	195/55R15		1); 2); 33)

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.