

**Prüfbericht 366-0027-16-WIRD
zur Erteilung der ECE (E1) 124R- 001057**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 13454100-10

Stand: 27.01.2016



Seite: 1 von 1

Manufacturer : RENAULT**Wheel dates:**

Wheel size according to standard : (45)

Off set(mm) : 36

Hole circle (mm)/number of holes : 100/4

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-950	R1-950	Without	60		385	1670	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : RENAULT

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 90 Nm for Type : B/C 57
100 Nm for Type : C06; 57commercial type: **RENAULT CLIO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
B/C 57	F543	40	145/70R13		1); 2); 33)
			155/70R13		
57	e2*93/81*0064*..	40-43	155/70R13		1); 2); 33)

commercial type: **RENAULT TWINGO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
C06	e2*93/81*0071*..	40-43	145/70R13		1); 2); 33)
			155/70R13		
C06	e2*98/14*0071*..	43	145/70R13 71		1); 2); 33)
			155/70R13 75		
C06	G391	40	145/70R13		1); 2); 33)
			155/70R13		

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.