

ALPINE® Gear Oil 85W-90 LS

Special hypoid gear oil

Properties

ALPINE Gear Oil 85W-90 LS is prescribed for highly stressed hypoid toothed drive axles with self-locking differentials.

ALPINE Gear Oil 85W-90 LS contains special additives to limit slip (limited slip) and prevent noise when driving around bends.

- special suitability for multi-disc limited slip differentials
- Excellent corrosion, rust and wear protection
- low foaming formation
- neutral to seals and non-ferrous metals

Application notes

ALPINE Gear Oil 85W-90 LS meets all performance requirements of hypoid gears with multi-disc limited slip differentials. Combined manual and axle transmissions can be supplied as well as vehicles with transfer cases.

ALPINE Gear Oil 85W-90 LS can also be used in all drive axles with API GL-5 requirements in order to reduce the number of grades.

Service description

Specifications:

- API GL-5 / LS
- MIL-L-2105 C/D
- ZF TE-ML 05

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE Gear Oil 85W-90 LS
Density at 15°C	DIN ISO 3675	kg/m ³	897
Viscosity at 40°C	DIN 51 562	mm ² /s	145
Viscosity at 100°C	DIN 51 562	mm ² /s	14.4
Viscosity Index (VI)	DIN ISO 2909	-	97
Viscosity at -26°C	ASTM D2983	-mPa.s	130,000
Pour point	DIN ISO 3016	°C	-30
Flash point COC	ASTM D92	°C	210

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.