

ALPINE® ATF MB 14

HC-Synthetic Automatic Transmission Fluid

Properties

- Top quality properties
- High load carrying capacity and extremely wear-reducing
- Superior friction value consistency
- No foam formation
- Lowest evaporation losses
- Soft switching operations even at medium temperatures
- Excellent viscosity-temperature behaviour
- Excellent oxidation and thermal stability
- Neutral towards common sealing materials

Application notes

- Especially for the new Mercedes-Benz 7-speed automatic transmission type 722.9, except code A89 and 5-speed automatic transmission with controlled torque converter lock-up clutch (KÜB) for vehicles with rear-wheel drive (722.6) ALPINE ATF MB 14 is downwards compatible with the previous Mercedes-Benz 4- and 5-speed passenger cars automatic transmissions (722.3, 722.4, 722.5), except the 5-speed CVT automatic transmission (722.7).

Observe manufacturer's instructions!

Service description

Recommendation*:

- **MB 236.14**

TYPICAL PARAMETERS	METHODS	UNITS	Alpine ATF MB 14
Thickness at 15°C	ASTM D4052	kg/m ³	850
Viscosity at 40°C	ASTM D445	mm ² /s	31.3
Viscosity at 100°C	ASTM D445	mm ² /s	6.3
Viscosity index (VI)	ASTM D2270		157
Pour point	ASTM D6892	°C	-45
Flash point COC	ASTM D92	°C	206
Colour			red

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.