

DURACELL®

TECHNICAL DATA SHEET

Type no.	DS 55
Article no.	010555190801
Standards	DIN EN 50342-1, 50342-2
Application	Starter battery
Electrical data	
Rated voltage	12V
Rated capacity	55 Ah (K20)
Cold start current	450 A (EN)
Dimensions and weights	
Box	LB2
Length max.	241mm
Width max.	175mm
Box height max.	175mm
Total height max.	175mm
Battery weight	Ca. 13,5 kg (+/- 5 %)
Electrolyte density	Approx. 1,28 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	72
Pallet ID	Euro pallet
Items per layer	18
Features	
Base hold-down	B13
Layout	0
Terminal	1
Separator	PE bag separator
Degassing	Battery with central degassing
Flame arrester	Integrated
Performance identification	W4 - C2 - V1 - E1
Maintenance 1)	
Water consumption	W4
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 3 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage 2)	max. 14,8 V



1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

