

DURACELL®

TECHNICAL DATA SHEET

Type no.		DS 70	
Article no.		010570440801	
Standards		DIN EN 50342-1, 50342-2	
Application		Starter battery	
Electrical data			
Rated voltage		12V	
Rated capacity		70 Ah (K20)	
Cold start current		640 A (EN)	
Dimensions and weights			
Box	LB3		
Length max.	278mm		
Width max.	175mm		
Box height max.	175mm		
Total height max.	175mm		
Battery weight	Ca. 17,0 kg (+/- 5 %)		
Electrolyte density		Approx. 1,28 kg/l	
Electrolyte		Diluted sulphuric acid	
Items/pallet		64	
Pallet ID		Euro pallet	
Items per layer		16	
Features			
Base hold-down		B13	
Layout		0	
Terminal		1	
Separator		PE bag separator	
Degassing		Battery with central degassing	
Flame arrester		Integrated	
Performance identification		W4 - C2 - V1 - E1	
Maintenance ¹⁾			
Water consumption		W4	
Refill water		Destilliert oder entmineralisiert (DIN 43530)	
Self-discharge		Ca. 3 % pro Monat	
Charging current		Ca. 1/10 der Nennkapazität	
Charging voltage ²⁾		max. 14,8 V	

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

