

DURACELL®

TECHNICAL DATA SHEET

Type no.	DL 72L	
Article no.	010955510801	
EAN/GTIN no.	9005753092228	
Application	Long-term discharge battery	
Electrical data		
Rated voltage	12V	
Rated capacity	55 Ah(K5), 72 Ah(K20), 85 Ah(K100)	
Dimensions and weights		
Box	D26	
Length max.	256mm	
Width max.	174mm	
Box height max.	205mm	
Total height max.	205mm	
Battery weight	Ca. 20,0 kg (+/- 5 %)	
Electrolyte density	Approx. 1,28 kg/l	
Electrolyte	Diluted sulphuric acid	
Items/pallet	51	
Pallet ID	Euro pallet	
Items per layer	17	
Features		
Base hold-down	B00	
Layout	1	
Terminal	1	
Separator	PE bag separator with glass nonwoven	
Degassing	Battery with central degassing	
Flame arrester	Integrated	
Maintenance 1)		
Water consumption	> 4g/Ah	
Refill water	Distilled or demineralised (DIN 43530)	
Self-discharge	Approx. 9 % per month	
Charging current	Approx. 1/10 of the rated capacity	
Charging voltage 2)	max. 14,4 V	



1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

