

DURACELL®

TECHNICAL DATA SHEET

| | | |
|-------------------------------|--|--|
| Type no. | DL 72L | |
| Article no. | 010955510801 | |
| Standards | DIN EN 50342-1, 50342-2 | |
| Application | Long-term discharge battery | |
| Electrical data | | |
| Rated voltage | 12V | |
| Rated capacity | 55 Ah(K5), 72 Ah(K20), 85 Ah(K100) | |
| Dimensions and weights | | |
| Box | D26 | |
| Length max. | 256mm | |
| Width max. | 174mm | |
| Box height max. | 205mm | |
| Total height max. | 205mm | |
| Battery weight | Ca. 20,0 kg (+/- 5 %) | |
| Electrolyte density | Approx. 1,28 kg/l | |
| Electrolyte | Diluted sulphuric acid | |
| Items/pallet | 51 | |
| Pallet ID | Euro pallet | |
| Items per layer | 17 | |
| Features | | |
| Base hold-down | B00 | |
| Layout | 1 | |
| Terminal | 1 | |
| Separator | PE bag separator with glass nonwoven | |
| Degassing | Battery with central degassing | |
| Flame arrester | Integrated | |
| Maintenance 1) | | |
| Water consumption | > 4g/Ah | |
| Refill water | Distilled or demineralised (DIN 43530) | |
| Self-discharge | Approx. 9 % per month | |
| Charging current | Approx. 1/10 of the rated capacity | |
| Charging voltage 2) | max. 14,4 V | |



1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

