

DURACELL®

TECHNICAL DATA SHEET

Type no.	DE 60 EFB
Article no.	012560110801
Standards	DIN EN 50342-1, 50342-2
Application	Starter battery start-stop
Electrical data	
Rated voltage	12V
Rated capacity	60 Ah (K20)
Cold start current	560 A (EN)
Dimensions and weights	
Box L2	
Length max.	241mm
Width max.	175mm
Box height max.	190mm
Total height max.	190mm
Battery weight	Ca. 16,5 kg (+/- 5 %)
Electrolyte density	Approx. 1,28 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	72
Pallet ID	Euro pallet
Items per layer	18
Features	
Base hold-down	B13
Layout	0
Terminal	1
Separator	PE bag separator with glass nonwoven
Degassing	Battery with central degassing
Flame arrester	Integrated
Performance identification	W4 - C2 - V3 - M2 (E3)
Maintenance ¹⁾	
Water consumption	W4
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 3 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage ²⁾	max. 14,8 V



¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

