

ALPINE® RS 0W-40 Ultra

High-performance low viscosity engine oil

Properties

ALPINE RS 0W-40 Ultra is a high-performance, low-friction engine oil for the highest requirements of powerful gasoline engines in cars. Excellent flow properties guarantee excellent cold start behavior. The exceptional high-temperature stability ensures a highly resilient lubricating film even under the most extreme conditions.

Using state-of-the-art technology, **ALPINE RS 0W-40 Ultra** ensures excellent wear protection and exceptional engine cleanliness, which extends the service life of the engine.

Application notes

ALPINE RS 0W-40 Ultra is a top product for high-performance engines with GPF (gasoline particulate filter) and offers extended protection against pre-ignition (LSPI).

Observe manufacturer's instructions!

This product is not backwards compatible with Porsche A40, C30, C20 or other Porsche specifications.

Service description

Specifications:

- ACEA C3
- API SN / API SN Plus

Recommendation*:

- Porsche C40
- VW 511 00
- MB 229.51 / MB 229.52
- GM dexos2™
- Fiat 9.55535-S2

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE RS 0W-40 Ultra
Density at 15°C	DIN 51 757	kg/m ³	846
Viscosity at 40°C	DIN 51 562	mm ² /s	72.4
Viscosity at 100°C	DIN 51 562	mm ² /s	14.1
Viscosity Index (VI)	DIN ISO 2909	-	204
HTHS-Viskosity	ASTM D4683	mPa.s	3.8
Pour point	DIN ISO 3016	°C	-48
Flash point COC	DIN ISO 2592	°C	230

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.