

ALPINE® C48

Premium coolant

Properties

ALPINE C48 is a coolant based on ethylene glycol, free of potentially harmful substances such as nitrites, amines and phosphates. Due to an optimal combination of inhibitors based on carboxylic acid technology as well as silicates and borates (hybrid coolant), **ALPINE C48** guarantees powerful and long-lasting corrosion protection for extended coolant life. Further additives prevent the coolant from foaming, provide the right cavitation protection and prevent deposits. **ALPINE C48** offers year-round, maintenance-free frost and overheating protection due to a higher boiling point. The coolant has no negative influence on coolant hoses or cylinder head gaskets.

Application notes

ALPINE C48 mixed with the corresponding quantity of (distilled) water is used as a coolant and heat transfer fluid in combustion engines, without restriction whether engines are made of cast iron, aluminium or a combination of both metals and in cooling systems made of aluminium or copper alloys. An application concentration of 50 vol.% is recommended all year round. Mixing **ALPINE C48** with other coolants or products of other manufacturers is not recommended.

Caution: Observe manufacturer's instructions and use concentration of min. 33 vol.%.

Service description

Specifications:

- AS 2108-2004
- ASTM D 3306, ASTM D 4985
- BS6580:2010
- CUNA NC 956-16
- AFNOR NFR 15-601
- JIS K 2234:2206
- SAE J1034
- ÖNORM V 5123
- SANS 1251:2005
- China GB 29743-2013

Approval:

- DTFR 29C100 (325.0)
- VW TL 774 C
- MAN 324 Typ NF
- Deutz DQC CA-14
- MTU MTL 5048

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

ALPINE® C48

Recommendation*:

- 2G
- BMW LC-87
- Deutz-Fahr (<03/2017)
- Eicher Engines (TMTL Part No. 93183798)
- Fendt
- Huerlimann (<03/2017)
- Jenbacher (TA-Nr. 1000-0201)
- Lamborghini-Tractors (<03/2017)
- Liebherr (Minimum LH-00-COL3A)
- MAN Energy Solutions (Liste 3.3.7)
- DTFR 29D100 (326.0)
- Mitsubishi Carisma (1996-2004)
- Mitsubishi Colt (2004-2007)
- MWM (TR 2091)
- Opel GM B 040 0240
- Porsche (<1995)
- Saab (690 1599)
- Same (<03/2017)
- Tesla (>2013)
- Volvo Trucks (TR 1286083)

Also protects:

- Alfa Romeo (1976-2005)
- ATLAS
- Bentley (1980-2005)
- Ferrari (1979-2009)
- Fiat (1982-2005)
- Ford (<1997)
- Jaguar (1986-1999)
- Lada
- Lancia (1976-2005)
- Lotus (1980-1999)
- Morgan
- Toyota (>2015)

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE C48
Density at 20°C	ASTM D 5931	g/cm ³	1.121 - 1.123
Reserve alkalinity (pH 5.5)	ASTM D 1121	ml 0,1 n HCl	13-15
Boiling point	ASTM D 1120	°C	>165
pH value	ASTM D 1287	-	7.1 - 7.3
Flash point	DIN EN ISO 2592	°C	>120
Antifreeze at 50 vol.%	ASTM D 1177	°C	- 36
Colour	-	-	blue-green

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.