

## Product Specification

### CO20W-30 U.T.T.O. 80W Lubricating Oil for Agricultural and Earth Moving Machinery

5 L	20 L	60 L	200L
CO20W30UTTO80W-5	CO20W30UTTO80W-20	CO20W30UTTO80W-60	CO20W30UTTO80W-200

#### LEVELS OF QUALITY

The lubricant **CO20W-30 U.T.T.O. 80W** complies with the following international specifications:

API GL-4; ALLISON C4; CAT TO-2; John Deere J20C; Massey-Fergusson M1135

#### DESCRIPTION

**CO20W-30 U.T.T.O. 80W** is a multifunctional lubricant (U.T.T.O. – Universal Tractor Transmission Oil) for hydraulic transmissions and systems of earthmoving equipment and agricultural machineries in general. It provides high anti-wear properties, anti-stick and anti-slip properties which allow the best effectiveness of the braking system. The formulation guarantees a reduction in power consumption and improves the efficiency of the hydraulic circuit

#### APPLICATIONS

**CO20W-30 U.T.T.O. 80W** is a multifunctional product to be used on gear changes, brake transmissions and oil bath, lateral reducers, wheel reducers, differential gears, hydraulic lifts, driving pulley, mechanical and hydrostatic guide of all agricultural machineries and earthmoving equipment, whenever a product with good performance levels is required.

SAE Scale		80W/20W-30
Density at 15°C.Kg/dm <sup>3</sup>	ASTM D1298	0.875
Viscosity at 100°C.cSt	ASTM D445	10.3
Viscosity Index	ASTM D2270	132
Flammability V.A.°C	ASTM D92	210
Pour Point °C	ASTM D97	-24

The above-mentioned values are indicative of production average values and are not an integral part of the specification.

**TDS Comline 20W-30 U.T.T.O. 80W\_REV.2 April 2021**

Comline Auto Parts Ltd

Unit B1 Luton Enterprise Park, Sundon Park Road, Luton, Bedfordshire, LU3 3GU, Great Britain

T: +44 1582 578 888 | F: +44 1582 578 889