



| | | | |
|-------------|---|-----------|-------------------|
| NAME | DP-EU008 Electrical Specifications | NO | DP-1-4-008 |
|-------------|---|-----------|-------------------|



| PARAMETERS AND CONDITIONS | SYMBOLS | MIN. | TYP. | MAX. | UNITS |
|--|-----------------|------|------|-------|-------|
| Storage Temperature Range | T _{ST} | -40 | | 150 | °C |
| Operating Temperature Range | T _{OP} | -40 | | 125 | °C |
| Pressure Range | P _r | 93.3 | | 258.3 | KPa |
| Supply Voltage | V _{Sv} | 4.8 | | 5.2 | V |
| Supply Current | I _{sc} | | 10 | | mA |
| Accuracy @ 25°C | %FS | -3 | | +3 | %FS |
| The DPF voltage output at 25°C (@ Supply Voltage (Vs) = 5.0Vdc, rated pressure = 101.3KPa) | V | 0.21 | 0.51 | 0.81 | V |

| | | | | | | |
|-----------------------|-------------------------|---------|------------|--------|----------|--------------------|
| 2021.03.25 | | 1 | 王亮 | 呂漢榮 | 黃鵬 | MOBILETRON |
| Date of first edition | Date of revised edition | edition | Manuscript | Review | Approval | Mar.30.2021 |
| | | | | | | Release |