


<b>NAME</b>	<b>DP-EU012 Electrical Specifications</b>	<b>NO</b>	<b>DP-1-4-013</b>
-------------	---	-----------	-------------------


**Picture**



**Plug**



**Drawing and Dimension**



PARAMETERS AND CONDITIONS	SYMBOLS	MIN.	TYP.	MAX.	UNITS
<b>Storage Temperature Range</b>	$T_{ST}$	-40		150	°C
<b>Operating Temperature Range</b>	$T_{OP}$	-40		125	°C
<b>Pressure Range</b>	$P_r$	80.3		206.3	KPa
<b>Supply Voltage</b>	$V_{Sv}$	4.8		5.2	V
<b>Supply Current</b>	$I_{sc}$		10		mA
<b>Accuracy @ 25°C</b>	%FS	-3		+3	%FS
<b>The DPF voltage output at 25°C</b> (@ Supply Voltage ( $V_s$ ) = 5.0Vdc, rated pressure = 101.3KPa)	$V$	0.73	1.03	1.33	V

<b>2021.06.03</b>		<b>1</b>	<b>王亮</b>	<b>呂漢榮</b>	<b>黃鵬</b>	<b>MOBILETRON</b>
<b>Date of first edition</b>	<b>Date of revised edition</b>	<b>edition</b>	<b>Manuscript</b>	<b>Review</b>	<b>Approval</b>	<b>Jun.08.2021</b>
						<b>Release</b>