


| | | | |
|-------------|--|-----------|-------------------|
| NAME | MS-E113 Electrical Specifications | NO | MS-1-4-161 |
|-------------|--|-----------|-------------------|


Picture



Plug



Drawing and Dimension



| PARAMETERS AND CONDITIONS | SYMBOLS | MIN. | TYP. | MAX. | UNITS |
|---|-----------------|------|------|------|-------|
| Storage Temperature Range | T _{ST} | -40 | | 150 | °C |
| Operating Temperature Range | T _{OP} | -40 | | 125 | °C |
| Pressure Range | Pr | 7 | | 120 | KPa |
| Supply Voltage | V _{Sv} | 4.8 | | 5.2 | V |
| Supply Current | I _{sc} | | 10 | | mA |
| Accuracy @ 25°C | %FS | -3 | | +3 | %FS |
| The MAP voltage output at 25°C (@ Supply Voltage (Vs) =5.0Vdc, rated pressure = 101.3KPa) | V | 3.67 | 3.97 | 4.27 | V |

| | | | | | | |
|-----------------------|-------------------------|---------|------------|--------|----------|-------------------|
| 2021.10.27 | | 1 | 汪芳波 | 王亮 | 黄鹏 | MOBILETRON |
| Date of first edition | Date of revised edition | edition | Manuscript | Review | Approval | Nov.01.2021 |
| | | | | | | Release |