



NAME	MS-U007 Electrical Specifications	NO	MS-1-4-017
-------------	--	-----------	------------



PARAMETERS AND CONDITIONS	SYMBOLS	MIN.	TYP.	MAX.	UNITS
Storage Temperature Range	T _{ST}	18	23	28	°C
Operating Temperature Range	T _{OP}	-40		125	°C
Pressure Range	Pr	0		130	KPa
Supply Voltage	V _{Sv}	0.005		4.99	V
Supply Current	I _{sc}		10		mA
Accuracy @ 25°C	%FS	-3		+3	%FS
The MAP voltage output at 25°C (@ Supply Voltage (VS) = 5.0Vdc, rated pressure =75 KPa)	V	2.67	2.97	3.27	V
The MAP voltage output at 25°C (@ Supply Voltage (Vs)=5.0Vdc, rated pressure = 101.3KPa)	V	3.74	4.04	4.34	V
The MAP voltage output at 25°C (@ Supply Voltage (Vs) =5.0Vdc, rated pressure = 112KPa)	V	4.20	4.50	4.80	V

2020.09.24		1	呂漢榮	王亮	黃鵬	MOBILETRON
Date of first edition	Date of revised edition	edition	Manuscript	Review	Approval	Sep.29.2020
						Release