

<b>NAME</b>	<b>RN-79 Electrical Specification</b>	<b>NO</b>	<b>RX-1-1-1064</b>
-------------	---------------------------------------	-----------	--------------------

<p><b>Picture</b> <span style="float: right;">OD : 132mm</span></p>	<p><b>Diagram</b></p>
---	-----------------------

PARAMETERS AND CONDITIONS		SYMBOLS	MIN.	TYP.	MAX.	UNITS
Storage Temperature Range		Tsto	-40	...	150	°C
Operating Temperature Range		Tope	-30	...	125	°C
Output Diodes	Avalanche Voltage Range (Diodes $\Delta Vz \leq 2V$ )	Vrm	19	...	24	V
	Average Rectified Forward Current	Io	50	...	...	A
	Maximum Instantaneous Forward Voltage @ If= 100A , T = 25°C	Vf	...	...	1.2	V
	Maximum Reverse Current @ Vrm = 16V	Ir	...	...	1.0	μA
Diodes Trio	Peak Repetitive Reverse Voltage	Vrm	...	...	...	V
	Average Rectified Forward Current	Io	...	...	...	A
	Maximum Instantaneous Forward Voltage @ If= 3A , T = 25°C	Vf	...	...	...	V
	Maximum Reverse Current at Vrm	Ir	...	...	...	μA

Component	Rating	Tolerance	Remark	Unit
Condenser	N.A.	±10%	...	μF
Resistor	N.A.	±5%	...	Ω

Reliability Test	Repetitive Thermal Shock	The Rectifier shall be designed to withstand 500 cycles of -30°C to 125°C in 20minutes and 125°C to -30°C in 20 minutes.
	The High Temp. Test	The Rectifier shall be designed to operate reliability at the rated current of alternator is 80% to 100% and at 6000 rpm ( shaft speed ) for a minimum of 10 hours at 125°C .
	Load Dump	The Rectifier shall withstand a voltage peak and noise from load dump transients without failure . Test condition : ON/OFF switch per 10 seconds while the rated current of alternator is 80% to 100% at 6000 rpm and test 200 times .
Mechanical Shock	Drop Shock	The Rectifier shall withstand a free fall from one meter onto a cement floor on each of the 3 main axes (x,y,z) two times without failure or performance degradation .
	Vibration Shock	The Rectifier shall withstand a vibration according to the following condition without failure or performance degradation . Condition : amplitude acceleration = 15G , vibration frequency = 10-500Hz , a period of 15 minutes for each of the 3 main axes (x,y,z) , test times = 16 cycle .
	Salt Spray	The Rectifier shall withstand 8 hours immersion in the solution = 5% of salt water at 35°C without failure or performance degradation .

2017.06.30		1	傅棟青			<b>MOBILETRON</b>
Date of first edition	Date of revised edition	Edition	Manu-script	Review	Approval	Jun.30.2017
						Release