

NAME	VR-H2000-76B Electrical Specification	NO	VR-1-1-1174
-------------	--	-----------	--------------------

<p align="center">Regulation System Connection Wire Diagram</p>	<p>System Regulator Type:</p> <ul style="list-style-type: none"> • Voltage Set Point :28.5V • Regulation : A - Circuit • Inactive Lamp • Short Circuit Protection • Soft- Start
--	---

PARAMETERS AND CONDITIONS	SYMBOLS	MIN.	TYP.	MAX.	UNITS
Operating Temperature Range	T_{OP}	-40	---	125	°C
Field	I_F		5		A
Voltage Set Point (2500 RPM, at 20A load)	V_{SET}	28.2	28.5	28.8	V
Secondary Set Point (2500 RPM ,at 20A load)	V_{SET2}	---	---	---	V
Speed Regulation (2000 RPM to 6000 RPM ,at load = 15A)	V_{SR}	---	---	-0.3	V
Load Regulation (10% to 95% ,at Speed = 6000 RPM)	V_{LR}	---	-0.8	-1.0	V
Saturation Voltage @ 5A, 24Volts	V_{SAT}	---	1.3	1.5	V
Standby Current (Key off, $V_{BAT} = 25.2V$)	I_{SB}	---	---	0.5	mA
Temperature Coefficient	T_C	-6	-3	0	mV/°C
Over voltage Indication	V_{OV}	31.0	32.0	33.0	V
Under voltage Indication	V_{UV}	18.0	19.0	20.0	V
Soft-Start Duty	D_{SS}	15	30	45	%
Cut in Speed	R_{CIS}	---	---	1300	rpm

Safety Characteristics:

- **Over voltage :** $V_s = 48 V$, 60 sec. from the ignition SW. is turned ON/OFF without failure.
- **Battery Reversal :** $V_s = -48 V$, 60 sec. from accidental battery reversal without failure.
- **Short Circuit Protection :** The regulator stands short circuit of Field and Lamp without failure.
- **Repetitive Thermal Shock :**
The Regulator shall be designed to withstand 500 cycles of -30°C to 125°C in 20 minutes and 125°C to -30°C in 20 minutes.
- **High Temperature Test :**
The Regulator shall be designed to operate reliability at the rated current of alternator is 80% to 100% and at 6000 rpm (shaft speed) for a minimum of 10 hours at 125°C.

2011 05.05.		1	卓建廷			MOBILETRON
Date of first edition	Date of revised edition	Edition	Manu-script	Review	Approval	May.10.2011
						Release