

NAME	VR- H2005-236 Electrical Specification	NO	VR-1-1-2022
-------------	---	-----------	--------------------

<p>Regulation System Connection Wire Diagram</p>	<p>System Regulator Type:</p> <ul style="list-style-type: none"> ● Voltage Set Point :14.3V ● Regulation : B - circuit ● Inactive Lamp ● Soft Start , 12sec LRC ● Short Circuit Protection ● FR Terminal connected to Computer
---	---

PARAMETERS AND CONDITIONS	SYMBOLS	MIN.	TYP.	MAX.	UNITS
Operating Temperature Range	T_{OP}	-30	---	125	°C
Field	I_F	---	5	---	A
Voltage Set Point (2500 RPM ,at 20A load)	V_{SET}	14.10	14.30	14.50	V
Secondary Set Point (2500 RPM ,at 20A load)	V_{SET2}	---	---	---	V
Computer Set Point	V_{SEC}	12.1	12.6	13.1	
Speed Regulation (2000 RPM to 6000 RPM ,at load = 15A)	V_{SR}	---	-0.1	-0.3	V
Load Regulation (10% to 95% ,at Speed = 6000 RPM)	V_{LR}	---	-0.3	-0.5	V
Saturation Voltage @ 5A, 12Volts	V_{SAT}	---	0.4	0.5	V
Standby Current (Key off, $V_{BAT} = 12.6V$)	I_{SB}	---	---	1.0	mA
Temperature Coefficient	T_C	-6	-3	0	mV/ °C
Over voltage Indication	V_{OV}	---	---	---	V
Under voltage Indication	V_{UV}	---	---	---	V
Soft-Start Duty	D_{SS}	15	30	45	%
LRC Delay Time(@<3800rpm)	T_{LRC}	10	12	14	Sec
Cut-in Speed	R_{CIS}	---	---	1400	RPM

Safety Characteristics:

- **Over voltage :** $V_s = 24 V$, 60 sec. from the ignition SW. is turned ON/OFF without failure.
- **Short Circuit Protection :** The regulator stands short circuit of Field without failure.
- **Repetitive Thermal Shock :**
The Regulator shall be designed to withstand 500 cycles of -30°C to 125 °C in 20 minutes and 125 °C to -30 °C in 20 minutes.
- **High Temperature Test :**
The Regulator shall be designed to operate reliability at the rated current of alternator is 80% to100% and at 6000 rpm (shaft speed) for a minimum of 10 hours at 125 °C .

2021.08.24		1	王毅賢	陳建文	陳建文	MOBILETRON
Date of first edition	Date of revised edition	Edition	Manu-script	Review	Approval	Aug.27.2021
						Release