

ACDelco

PREMIUM HP LONGLIFE SYNTHETIC 5W40 dexos2[®] ENGINE OIL



ENGINEERED FOR PERFORMANCE



PRODUCT DESCRIPTION

ACDelco Premium HP Long Life Synthetic 5W-40 dexos2[™] is an ultra-premium synthetic engine oil designed to provide outstanding levels of performance in passenger cars, SUV's and light commercial vehicles.

It is also formulated to be used in vehicles with exhaust gas after treatment systems such as catalysis or particulate filters.

FEATURES & BENEFITS

- Designed to fulfil the viscosity requirements of Series 1 Holden Captiva, Epica or Cruze Diesel
- Protects exhaust gas after treatment systems
- Excellent wear protection with maximum power output
- Protection against sludge and deposits in engines & turbochargers
- Applicable for diesel and petrol engines

APPLICATIONS

ACDelco dexos2[™] is General Motors and Holden service fill for many diesel engines fitted with diesel particulate filters and naturally aspirated petrol engines.

Recommended by ACDelco for use in;

- BMW vehicles requiring Long-life Oil 01
- Mercedes-Benz vehicles requiring MB-Approval 229.3
- Porsche vehicles requiring A40
- Renault vehicles requiring RN0710 / RN0700
- Volkswagen vehicles requiring VW 502 00 and VW 505 00

Look out for the application symbols across the ACDelco engine oil range. These will help you quickly find the spec you need.



For your nearest ACDelco Automotive Parts Stockist
call **1800 ACDelco** or visit **acdelco.com.au**

ACDelco

ACDelco

PREMIUM HP LONGLIFE SYNTHETIC 5W40 dexos2[®] ENGINE OIL



ENGINEERED FOR PERFORMANCE



PROPERTIES & SPECIFICATIONS

Approvals:

- dexos2[®]

Meets or exceeds the requirements of:

- API SN/CF, ACEA C3

Recommended for use in applications requiring:

- BMW Long-life Oil 01
- MB-Approval 229.3
- Porsche A40
- Renault RN0710 / RN0700
- Volkswagen VW 502 00 and VW 505 00

ACDelco P/N	Size (L)
19375068	5
19375069	20
19375070	208

Properties:

- SAE Grade 5W-40
- Viscosity, ASTM D 445
- 83 cSt @ 40° C
- 14.0 cSt @ 100° C
- Viscosity Index, 174 ASTM D 2270
- Sulfated Ash, 1.0 wt%, ASTM D 874
- HTHS Viscosity, 3.7 mPa•s @ 150° C, ASTM D4683
- Pour Point, -42°C, ASTM D 97
- Flash Point, 232°C, ASTM D 92
- Density @15° C, 0.860 kg/l, ASTM D 4052

HEALTH & SAFETY

Material Safety Data Sheets (MSDS) are available for download at www.acdelco.com.au

This product should not be used for purposes other than its intended use.

If disposing of used product, take care to protect the environment.



For your nearest ACDelco Automotive Parts Stockist
call **1800 ACDelco** or visit acdelco.com.au

ACDelco