



TECHNICAL DATA SHEET

AUTO-TRANS CVT

Product Type SYNTHETIC TRANSMISSION FLUID
Product Code N316

Description

Premium synthetic transmission fluid formulated to provide maximum protection and lubrication of the Continuous Variable Transmission (CVT) gearbox in a wide range of passenger cars, vans and commercial vehicles.

Benefits

- Exceptional shear stability
- Low temperature fluidity
- Low foaming
- Excellent oxidation resistance
- Anti-shudder durability
- Excellent wear protection

Specifications

Always check the owner's manual for the correct oil specification to use.

- BMW 8322 0 136 376 (EZL 799), 8322 0 429 154 (EZL 799A)
- Daihatsu Ammix CVTF-DC
- Dodge / Jeep NS-2, CVT 4
- Ford WSS-M2C9933A (CFT 30), Mercon C, CFT
- GM Dex-CVT, GM CVT
- Honda HMMF, HCF-2
- Hyundai / Kia SP-CVT1
- Mazda JWS 3320
- Mercedes-Benz MB 236.20
- Mitsubishi DiaQueen CVTF-J1
- Nissan NS-1, NS-2
- Subaru CVTF, CVTF II, K0425Y0710, E-CVTF, i-CVTF
- Mini Cooper EZL 799, EZL 799A, ZF CVT V1
- Suzuki CVTF3320, CVT Fluid Green 1



TECHNICAL DATA SHEET

AUTO-TRANS CVT

Product Type SYNTHETIC TRANSMISSION FLUID
Product Code N316

Typical Properties

Color	Visual	-	Red
Viscosity @ 100°C	ASTM D-445	mm ² /s	5,8
Viscosity @ 40°C	ASTM D-445	mm ² /s	28
Viscosity Index	ASTM D-2270	-	160
Viscosity @ -40°C	ASTM D-5294	mPa.s	9773
Pour Point	ASTM D-664	°C	-54
Specific gravity	ASTM D-4052	-	0,843
Flash Point	ASTM D-92	°C	212

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Eskan Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDON

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu