



TECHNICAL DATA SHEET

80W-90 LS

Product Type 80W-90 MINERAL GEAR OIL
Product Code N336

Description

A specially formulated extreme pressure gear oil for use in limited slip differentials.

Benefits

- Reduces whining and chattering
- Excellent high temperature stability
- Ensures clutches slide smoothly
- Extreme pressure properties

Specifications

Always check the owner's manual for the correct oil specification to use.

- API GL-5 LS



TECHNICAL DATA SHEET

80W-90 LS

Product Type 80W-90 MINERAL GEAR OIL
Product Code N336

Typical Properties

SAE Viscosity Grade	SAE J306	-	80W-90
Viscosity @ 100°C	ASTM D-445	mm ² /s	14,3
Viscosity @ 100°C; After shearing	ASTM D-6278	mm ² /s	Stay-in-grade
Viscosity @ 40°C	ASTM D-445	mm ² /s	127,0
Viscosity Index	ASTM D-2270	-	113
Viscosity, @ -26°C	ASTM D-5293	mPa.s	<150000
TAN	ASTM D-664	-	2,70
Pour point	ASTM D-5950	°C	-33
Specific gravity	ASTM D-4052	-	0,890
Flash point	ASTM D-92	°C	218

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Eskan Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDON

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu