

SINGLE EXTRACTOR GROUP 5m Ø100mm 400V TRIPHASE

Reference : AG 0020



Item name	SINGLE EXTRACTOR GROUP 5m Ø100mm 400V TRIPHASE
EAN code	3701555301099
Intro	Specially designed for exhaust gas suction for LV workshops.
Text	This extractor is the easiest installation kit to install on a wall or on the front. The equipment allows to work in a healthy environment without inhalation of exhaust gases and in compliance with the safety standards at work.
Product highlight	Easy to install
Specifications	Specifications: - galvanized steel structure - electric motor, statically and dynamically balanced wheel, delivered with wall bracket and rubber funnel. - 5m of Ø100mm hose (-40° to +200°) made of high temperature EPDM vulcanized fabric on both sides. Completely anti-crushing structure, smooth inside and maintains flexibility over time thanks to the strong nylon spiral with a very tight pitch. This feature prevents the hose from stretching during pulling and from crushing in high stress situations. - delivery: Ø 125mm - power supply: 400V Tri - motor power: 0,5cv, 0,37KW, 50HZ, 1.0A - max flow: 450m3/h - noise level: 66dB - thermal protection switch

- rubber exhaust nozzle with watertight valve included in the body of the product, anti-intrusion network, clamp for fixing to the exhaust

Many options available, please consult us.

Warranty period	2 years
Vehicle type	LV
Decibel level	66.00 dB
Tension	400V
Diameter	100.00 mm
Air flow rate	450
Tariff code	Tariff Equipment (TE)
Type of gas extraction system	Fixed
DPF compatible	NO
Hose length (m)	5m
Hose diameter (mm)	100mm
Max. hose temperature (°C)	200°C



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to
12h30 and from 14h to 17h30
(16h30 on Friday)