



# intAct Active-Power AGM

Sealed maintenance-free AGM battery | electrolyte absorbed in glass fibre mats | wet charged

Art.No.

## AP-AGM180

Volt	12V
Capacity	180 AH (c20)
CCR -18°C (EN)	900 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	513 x 223 x 223 mm
Weight	55 kg
Pos. of Terminal	3
Terminal	1
Base plate	-

### Usage




### Professional all-rounder

Exceptional capacity with absorbed electrolyte and gas recombination. For consumers in long-distance buses and as intermediate storage for smaller solar and wind power plants. Our recommendation for all who are looking for a robust, inexpensive supply battery and have no desire for maintenance.


- » **Multifunctional battery for medium cyclical application.**  
400 cycles according to IEC 254-1.
- » 2 versions: **grid plate** or **spiral cells.**
- » Spiral cell with wound grids **for compact design and increased cold cranking performance** compared to conventional batteries with flat grids.
- » **Longer life expectancy** than conventional lead-acid batteries.
- » High vibration resistance.
- » **Sealed maintenance-free. VRLA Battery** with gas recombination and safety valves, where refilling is neither possible nor necessary.




Size



Pos. of Terminal 3



Terminal 1



Base plate -

As of 26.08.2024