

intAct BackUp-Power

Sealed maintenance-free calcium battery (Ca/Ca) | electrolyte absorbed in glass fibre mats (AGM) | wet charged

Art.No.

BU14

| | |
|---------------------|----------------------------|
| Volt | 12V |
| Capacity | 14 AH (c20) |
| CCR -18°C (EN) | 80 A (EN) |
| Electrolyte | diluted sulphuric acid |
| Electrolyte density | 1,28 +/- 0,01 Kg/l (25° C) |
| Size (LxWxH) | 151 x 98 x 101 mm |
| Weight | 3,85 kg |
| Pos. of Terminal | 3 |
| Terminal | screw terminal |
| Base plate | - |

Usage




Support for the starter battery

Supplies consumers in certain types of vehicles and keeps them charged during the start-up, thus protecting the electronics. Our recommendation as a reliable alternative to the original installed back-up battery.


- » Increased cold start performance.
- » Longer life expectancy. Three times more cycle resistant than conventional starter batteries.
- » Wet charged. Ready to use.
- » Sealed valve-regulated battery (VRLA) with gas recombination.
- » Sealed maintenance-free and leak-proof.
- » Electrolyte absorbed in glass fibre mat.
- » Lead-calcium alloy grid plates.




Size



Pos. of Terminal 3



Terminal screw terminal



Base plate -

As of 26.08.2024