



intAct Marine-Power AGM

Sealed AGM battery with grid plates | electrolyte fixed in fleece | filled and charged | absolutely maintenance-free

Art.No.

MP95-AGM

| | |
|---------------------|--|
| Volt | 12V |
| Capacity | 85 AH (c5), 95 AH (c20), 107 AH (c100) |
| CCR -18°C (EN) | - |
| Electrolyte | diluted sulphuric acid |
| Electrolyte density | |
| Size (LxWxH) | 260 x 171 x 210 mm |
| Weight | 26,5 kg |
| Pos. of Terminal | 1 |
| Terminal | F-M8 |
| Base plate | - |



Usage




Robust marine battery


AGM-based for high currents and deep charge cycles. Our recommendation for endurance, absolutely maintenance-free marine applications.

- » **Very high life expectancy.** 700 cycles according to IEC 254-1 for heavy cyclic use.
- » **Absolutely maintenance-free.** VRLA battery with gas recombination and safety valves, where refilling is not possible and not necessary.
- » **Constant power quality** throughout the discharge process even at high currents.
- » Longer **life** than wet lead-acid battery.
- » **Shorter charging time** than wet lead-acid battery.
- » **Low self-discharge.** Loses less than 3% charge per month.
- » **Vibration resistant AGM battery** with robust grids and strong fleece separators.
- » **Reinforced grid plates** with higher performance active material **for deep cycle applications.**
- » **Temperature and corrosion resistant case.**
- » **Can also be installed horizontally.**
- » **Leak-proof.**


Size



Pos. of Terminal 1



Terminal F-M8



Base plate -

As of 26.08.2024