



intAct Solar-Power AGM

Sealed AGM battery with grid plates | electrolyte fixed in fleece | filled and charged | absolutely maintenance-free

Art.No.

SP345-06-AGM

Volt	6V
Capacity	300 AH (c5), 315 AH (c20), 357 AH (c100)
CCR -18°C (EN)	-
Electrolyte	diluted sulphuric acid
Electrolyte density	
Size (LxWxH)	312 x 180 x 359 mm
Weight	45 kg
Pos. of Terminal	0
Terminal	F-M8
Base plate	-



Usage



Robust solar battery


on AGM-basis for high currents and deep charge cycles. Our recommendation if you want an enduring, absolutely maintenance-free battery for solar or wind applications.

- » **Very high life expectancy.** 700 cycles according to IEC 254-1 for heavy cyclic use.
- » **Absolutely maintenance-free.** VRLA battery with gas recombination and safety valves, where refilling is not possible and not necessary.
- » **Constant power quality** throughout the discharge process even at high currents.
- » Longer **life** than wet lead-acid battery.
- » **Shorter charging time** than wet lead-acid battery.
- » **Low self-discharge.** Loses less than 3% charge per month.
- » **Vibration resistant AGM battery** with robust grids and strong fleece separators.
- » **Reinforced grid plates** with higher performance active material **for deep cycle applications.**
- » **Temperature and corrosion resistant case.**
- » **Can also be installed horizontally.**
- » **Leak-proof.**


Size

Kasten: SP345-06-AGM

Pos. of Terminal 0



Terminal F-M8



Base plate -

As of 26.08.2024